

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name / designation MOTOROLJA 5W-40 SYNTET 162690101

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

NATIONAL MANUFACTURER/IMPORTER

Enterprise Luna Verktyg & Maskin AB
Postal code SE-441 80 ALINGSÅS
Country SVERIGE
Telephone + 46 322 60 60 00
Fax + 46 322 60 64 43

CONTACT PERSONS

Name	E-mail	Telephone	Country
Jörgen Bengtsson		+ 46 322 60 64 52	

2 Hazards identification

2.1 Classification of the substance or mixture

DPD Classification:

CLP Classification:

Most important HSE hazard effects:

2.2 Label elements

Signal word: None

EC-Label: No

COMPOSITION

KATALYTISKT HYDROISOMERICERADE KOLVÄTEN (> 60 %), Zinkdialkylditiofosfat (< 2 %), Styrenkolvätepolymer (< 2 %)

SUPPLEMENTAL HAZARD INFORMATION (EU)

Not classified.

2.3 Other hazards

3 Composition/information on ingredients

3.2 Mixtures

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	DPD-Classification	CLP-classification
KATALYTISKT HYDROISOMERICERADE KOLVÄTEN				> 60 %		
Zinkdialkylditiofosfat		272-028-3	68649-42-3	< 2 %	Xi,N,R36/38 - R51/53	Skin Irrit. 2 H315 Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Styrenkolvätepolymer				< 2 %	R53	Aquatic Chronic 4 H413

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

4 First aid measures

4.1 Description of first aid measures

INHALATION

Provide rest, warmth and fresh air. Rinse nose, mouth and throat with water. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Contact physician.

SKIN CONTACT

Wash skin with soap and water. Remove contaminated clothing. Get medical attention if any discomfort continues. Immediate hospital care if the product has been forced through the skin at high pressure.

EYE CONTACT

Rinse with water. Get medical attention if any discomfort continues.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

5 Fire-fighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

Fire may be extinguished using powder, foam or carbon dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA

Do not use water.

5.2 Special hazards arising from the substance or mixture

SPECIAL HAZARDS

In strong heat, combustible vapours are emitted. In the event of a fire, irritating smoke is formed. Carbon monoxide may be formed in the event of incomplete combustion.

5.3 Advice for fire-fighters

ADVICE FOR FIREFIGHTERS

Wear suitable respiratory protection.

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

OTHER INFORMATION

Only trained personnel may undertake fire fighting in enclosed spaces. Containers close to fire should be removed or cooled with water.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

PERSONAL PRECAUTIONS

Bank in the discharge. Use personal protective equipment.

6.2 Environmental precautions

ENVIRONMENTAL PRECAUTIONS

Prevent discharges into the sewage system, watercourses or lakes.

6.3 Methods and material for containment and cleaning up

METHODS AND MATERIAL

Bank with sand, earth or other inert absorption agent. Immediately inform the authorities if the emission reaches the sewage system and watercourses. Inform the emergency service in the event of major spillage. Remains and waste must be treated as dangerous waste. In the event of spillage into water: Enclose by booms and pump out as much as possible, collect minor quantities, e.g. in bark, and remove immediately.

6.4 Reference to other sections

7 Handling and Storage

7.1 Precautions for safe handling

PRECAUTION FOR SAFE HANDLING

Prevent spillage. Avoid formation of aerosol/mist.

7.2 Conditions for safe storage, including any incompatibilities

CONDITION FOR SAFE STORAGE, INCLUDING ANY UNCOMPATIBILITIES

Keep container dry.

7.3 Specific end uses

8 Exposure controls / Personal protection

8.1 Control parameters

OEL value

Ingredient name	CAS no.	Range	ppm	mg/m ³	Year	Notification
KATALYTISKT HYDROISOMERICERADE KOLVÄTEN		15 min.		3	2000	
KATALYTISKT HYDROISOMERICERADE KOLVÄTEN		8 h		1	2000	

R=Toxic for reproduction, H=Skin absorption, K=Carcinogenic, A=Sensitising, T=Upper limit, M=Mutagenic

BIOLOGICAL THRESHOLD VALUES

Contains mineral oil for which a threshold value for oil mist must be applied.

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Good personal hygiene is important. Use only in well-ventilated areas. Remove contaminated clothing. Do not put polluted rags in your pockets. Wear appropriate clothing to prevent any possibility of skin contact.

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

EYE PROTECTION

Use eye protection.

SKIN PROTECTION

Apron.

HAND PROTECTION

Protective gloves (nitrile rubber, fluorocarbon rubber).

9 Physical and chemical Properties

9.1 Information on basic physical and chemical properties

PHYSICAL STATE Liquid.

COLOUR Brownish.

ODOUR Oil. Weak.

SOLUBILITY Organic solvents.

Parameter	Value/unit	Method/reference	Observation
pH concentrate	No data		
pH in solution	No data		
Melting point	No data		
Freezing point	No data		
Initial boiling point and boiling range	No data		
Flash point	> 200 °C	ASTM D 92	
Evaporation rate	No data		
Flammability (solid, gas)	No data		
Flammability limits	No data		
Explosion limits	No data		
Vapour pressure	No data		
Vapour density	No data		
Relative density	No data		
Partition coefficient	No data		
Auto-ignition temperature	No data		
Decomposition temperature	No data		
Viscosity	~ 76 mm ² /s	40°C ASTM D 445	

9.2 Other safety information

Parameter	Value/unit	Method/reference	Observation
Density	~ 854 kg/m ³	15°C ASTM D 4052	

Note no.	Comments

10 Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

CHEMICAL STABILITY

Stable.

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

10.5 Incompatible materials

INCOMPATIBLE MATERIALS

Strong oxidizing agent.

10.6 Hazardous decomposition products:

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide may be formed in the event of incomplete combustion.

11 Toxicological information

11.1 Toxicological effects

ACUTE TOXICITY - ORAL

Risk of aspiration with chemical pneumonia.

ACUTE TOXICITY - DERMAL

Product that has come under the skin at high pressure may cause extensive subcutaneous necrosis.

ACUTE TOXICITY - INHALATION

Dust, vapours, mists or aerosol may cause irritation.

SERIOUS EYE DAMAGE/IRRITATION

May cause discomfort.

CARCINOGENICITY

May cause cancer after repeated exposure.

OTHER TOXICOLOGICAL INFORMATION

Used oils may contain contaminants hazardous to health. Protracted or repeated contact in combination with poor hygiene may cause skin problems in the form of skin inflammation (dermatitis), eczema and oil acne.

12 Ecological information

12.1 Toxicity

ACUTE AQUATIC TEST RESULTS

NOT TRANSLATED

12.2 Persistence and degradability

DEGRADABILITY

The principal constituents are expected to be biodegradable. Slowly biodegradable.

12.3 Bioaccumulative potential

ACCUMULATION

Contains component/components that can be bioaccumulated.

12.4 Mobility in soil

MOBILITY

The product floats on water. Contains components that strongly adsorb earth particles.

12.5 Results of PBT and vPvB assessment

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

12.6 Other adverse effects

OTHER EFFECTS

Forms an oil film on water surfaces that may harm aquatic organisms and may disturb the transport of oxygen at the air/water interface.

13 Disposal considerations

13.1 Waste treatment methods

GENERAL REGULATIONS

May only be transported by a contractor with a special licence.

CATEGORY OF WASTE

EWC 13 02 05

14 Transport information

Classified as Dangerous Goods: **No**

Land transport (ADR/RID)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Hazard label(s)	Not applicable.		
Hazard ID:	Not applicable.	Tunnel restriction code	Not applicable.

Inland water ways transport (ADN)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Environmentally hazardous in tank-vessels	Not applicable.		

Sea transport (IMDG)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Sub Risk:	Not applicable.		
IMDG Code segregation group	Not applicable.		
Marine pollutant	Not applicable.		
EMS:	Not applicable.		

SAFETY DATA SHEET

MOTOROLJA 5W-40 SYNTET 162690101

Last changed: 29/05/2012

Internal No: 162690101

Air transport (ICAO-TI / IATA-DGR)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Hazard label(s)	Not applicable.		

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical Safety Assessment

16 Other information

LIST OF RELEVANT R-PHRASES

R36/38	Irritating to eyes and skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.

LIST OF RELEVANT H-STATEMENTS

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.