

SAFETY DATA SHEET

VÅXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name / designation VÅXELLÅDSOLJA EP 220 155370109

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

NATIONAL MANUFACTURER/IMPORTER

Enterprise Luna Verktyg & Maskin AB
Postal code SE-441 80 ALINGSÅS
Country SVERIGE
Telephone + 46 322 60 60 00
Fax + 46 322 60 64 43

CONTACT PERSONS

Name	E-mail	Telephone	Country
Jörgen Bengtsson		+ 46 322 60 64 52	

2 Hazards identification

2.1 Classification of the substance or mixture

DPD Classification:

CLP Classification:

Most important HSE hazard effects:

2.2 Label elements

Signal word: None

EC-Label: No

COMPOSITION

Alkylamin (0,1 - 0,2 %), Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346) (> 90 %)

SUPPLEMENTAL HAZARD INFORMATION (EU)

Not classified.

2.3 Other hazards

3 Composition/information on ingredients

3.2 Mixtures

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

Ingredient name	Reg.No	EC No.	CAS No.	Conc. (wt%)	DPD-Classification	CLP-classification
Alkylamin				0,1 - 0,2 %	T,C,N,R22 - R23/24 - R34 - R43 - R48/20 - R50/53	Acute Tox. 3 H311 Acute Tox. 3 H331 Acute Tox. 4 H302 Skin Corr. 1B H314 Skin Sens. 1 H317 Aquatic Acute 1 H400 Aquatic Chronic 4 H413
Petroleum oil, highly refined (DMSO-EXTRAKT<3% IP346)				> 90 %		

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

4 First aid measures

4.1 Description of first aid measures

INHALATION

Fresh air and rest. Heat. Rinse nose, mouth and throat with water. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Contact physician.

SKIN CONTACT

Wash skin with soap and water. Remove contaminated clothing. Get medical attention if any discomfort continues. Product that has entered under the skin at high pressure demands immediate medical attention.

EYE CONTACT

Rinse with water. Get medical attention if any discomfort continues.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

5 Fire-fighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

Fire may be extinguished using powder, foam or carbon dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA

Do not use water.

5.2 Special hazards arising from the substance or mixture

SPECIAL HAZARDS

Evolves combustible gases if heated. In the event of a fire, irritating smoke is formed. Carbon monoxide may be formed in the event of incomplete combustion.

5.3 Advice for fire-fighters

ADVICE FOR FIREFIGHTERS

Wear suitable respiratory protection.

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

OTHER INFORMATION

Only trained personnel may undertake fire fighting in enclosed spaces. Containers close to fire should be removed immediately or cooled with water.

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

PERSONAL PRECAUTIONS

Use personal protective equipment.

6.2 Environmental precautions

ENVIRONMENTAL PRECAUTIONS

Prevent dispersion through damming with sand, earth or other suitable material. Prevent discharges into the sewage system, watercourses or lakes.

6.3 Methods and material for containment and cleaning up

METHODS AND MATERIAL

Collect. Immediately inform the authorities if the emission reaches the sewage system and watercourses. Inform the emergency service in the event of major spillage. Treat as dangerous waste. In the event of spillage into water: Enclose by booms and pump out as much as possible, collect minor quantities, e.g. in bark, and remove immediately.

6.4 Reference to other sections

7 Handling and Storage

7.1 Precautions for safe handling

PRECAUTION FOR SAFE HANDLING

Avoid formation of aerosol/mist. Prevent spillage.

7.2 Conditions for safe storage, including any incompatibilities

7.3 Specific end uses

8 Exposure controls / Personal protection

8.1 Control parameters

OEL value

Ingredient name	CAS no.	Range	ppm	mg/m3	Year	Notification
Petroleum oil, highly refined (DMSO-EXTRAKT < 3% IP346)		15 min.		3		
Petroleum oil, highly refined (DMSO-EXTRAKT < 3% IP346)		8 h		1		

R=Toxic for reproduction, H=Skin absorption, K=Carcinogenic, A=Sensitising, T=Upper limit, M=Mutagenic

OTHER INFORMATION REGARDING LIMIT VALUES AND MONITORING

Contains mineral oil for which a threshold value for oil mist must be applied.

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Good personal hygiene is important. Use only in well-ventilated areas. Remove contaminated clothing. Do not put polluted rags in your pockets.

EYE PROTECTION

Use eye protection.

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

SKIN PROTECTION

Apron.

HAND PROTECTION

Protective gloves (nitrile rubber, fluorocarbon rubber).

9 Physical and chemical Properties

9.1 Information on basic physical and chemical properties

PHYSICAL STATE Liquid.

COLOUR Yellowish.

ODOUR Oil. Weak. Sulphur.

SOLUBILITY Organic solvents.

Parameter	Value/unit	Method/reference	Observation
pH concentrate	No data		
pH in solution	No data		
Melting point	No data		
Freezing point	No data		
Initial boiling point and boiling range	No data		
Flash point	> 200 °C		
Evaporation rate	No data		
Flammability (solid, gas)	No data		
Flammability limits	No data		
Explosion limits	No data		
Vapour pressure	No data		
Vapour density	No data		
Relative density	No data		
Partition coefficient	No data		
Auto-ignition temperature	No data		
Decomposition temperature	No data		
Viscosity	~ 220 mm ² /s	40°C	

9.2 Other safety information

Parameter	Value/unit	Method/reference	Observation
Density	~ 894 kg/m ³	15°C	

Note no.	Comments

10 Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

CHEMICAL STABILITY

Stable under recommended storage and handling conditions.

10.3 Possibility of hazardous reactions

POSSIBILITY OF HAZARDOUS REACTIONS

Strong oxidizing agent.

10.4 Conditions to avoid

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

10.5 Incompatible materials

10.6 Hazardous decomposition products:

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide and hydrocarbons are emitted in a fire.

11 Toxicological information

11.1 Toxicological effects

ACUTE TOXICITY - ORAL

Risk of aspiration with chemical pneumonia.

ACUTE TOXICITY - INHALATION

Oil mist may irritate the respiratory organs.

SKIN CORROSION/IRRITATION

Protracted or repeated contact in combination with poor hygiene may cause skin problems in the form of skin inflammation (dermatitis), eczema and oil acne. The product used may contain compounds that are harmful to health that have formed during use. Product that has come under the skin at high pressure may cause extensive subcutaneous necrosis.

SERIOUS EYE DAMAGE/IRRITATION

May cause discomfort.

12 Ecological information

12.1 Toxicity

ECOTOXICITY

Forms an oil film on water surfaces that may harm aquatic organisms and may disturb the transport of oxygen at the air/water interface.

12.2 Persistence and degradability

DEGRADABILITY

The principal constituents are expected to be biodegradable. Slowly biodegradable.

12.3 Bioaccumulative potential

ACCUMULATION

Bioaccumulation can be expected.

12.4 Mobility in soil

MOBILITY

Low solubility in water. The product floats on water. Contains components that strongly adsorb earth particles.

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

13 Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

GENERAL REGULATIONS

May only be transported by a contractor with a special licence.

CATEGORY OF WASTE

EWC 13 02 05

14 Transport information

Classified as Dangerous Goods: **No**

Land transport (ADR/RID)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Hazard label(s)	Not applicable.		
Hazard ID:	Not applicable.	Tunnel restriction code	Not applicable.

Inland water ways transport (ADN)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Environmentally hazardous in tank-vessels	Not applicable.		

Sea transport (IMDG)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Sub Risk:	Not applicable.		
IMDG Code segregation group	Not applicable.		
Marine pollutant	Not applicable.		
EMS:	Not applicable.		

Air transport (ICAO-TI / IATA-DGR)

14.1 UN-No.	Not applicable.	14.4 Packing group	Not applicable.
14.2 Proper Shipping Name	Not applicable.	14.5 Environmental hazards	Not applicable.
14.3 Class(es)	Not applicable.		
Hazard label(s)	Not applicable.		

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or

SAFETY DATA SHEET

VÄXELLÅDSOLJA EP 220 155370109

Last changed: 23/04/2012

Internal No: 155370109

mixture

15.2 Chemical Safety Assessment

16 Other information

LIST OF RELEVANT R-PHRASES

R22	Harmful if swallowed.
R23/24	Toxic by inhalation and in contact with skin.
R34	Causes burns.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LIST OF RELEVANT H-STATEMENTS

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H413	May cause long lasting harmful effects to aquatic life.