

GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name / designation GASBEHÅLLARE ACETYLEN 21150107

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

NATIONAL MANUFACTURER/IMPORTER

Enterprise AGA GAS AB
Postal code 181 81 LIDINGÖ
Telephone +46 8 706 95 88

2 Hazards identification

2.1 Classification of the substance or mixture

DPD Classification: F+; R12, R5, R6

CLP Classification: Flam. Gas 1H220, Org. Perox. AH240, EUH006

effects: without contact with air.

2.2 Label elements



Signal word: None

EC-Label: No

COMPOSITION

Acetylen, etyn (> 99,5 %)

H Statements

H220 Extremely flammable gas.
H240 Heating may cause an explosion.

EUH006 Explosive with or without contact with air.

P Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P403 Store in a well-ventilated place.

2.3 Other hazards

3 Composition/information on ingredients

3.2 Mixtures



GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

| Ingredient name | Reg.No | EC No. | CAS No. | Conc. (wt%) | DPD-Classification | CLP-classification |
|-----------------|--------|-----------|---------|----------------|--------------------|--|
| Acetylen, etyn | | 200-816-9 | 74-86-2 | > 99,5 % | | Flam. Gas 1 H220 Self-react. A H240 EUH006 |

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

4 First aid measures

4.1 Description of first aid measures

INHALATION

Move the exposed person to fresh air at once. Use compressed air breathing apparatus. Keep the injured person warm and relaxed. Summon physician.Administer breathing assistance, if necessary.

4.2 Most important symptoms and effects, both acute and delayed

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

High concentrations may cause asphyxia. Unconsciousness. Asphyxiation may occur without forewarning. May give rise to symptoms such as dizziness, headache, nausea and ataxia.

4.3 Indication of any immediate medical attention and special treatment needed

5 Fire-fighting measures

5.1 Extinguishing media

SUITABLE EXTINGUISHING MEDIA:

All common fire extinguishing agents may be used.

EXTINGUISHING METHODS

Stop flow of gas or liquid if possible. Do not extinguish burning gas discharge. Be aware of risk of fire re-starting, and risk of explosion. Containers close to fire should be removed immediately or cooled with water.

5.2 Special hazards arising from the substance or mixture

SPECIAL HAZARDS

Containers may explode if heated. Carbon monoxide may be formed in the event of incomplete combustion.

5.3 Advice for fire-fighters

ADVICE FOR FIREFIGHTERS

Use protective equipment and compressed air breathing apparatus.

OTHER INFORMATION

Extremely flammable

6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

PERSONAL PRECAUTIONS

Use compressed air breathing apparatus. Evacuate area endangered by gas. Provide good ventilation. Eliminate all sources of ignition.

6.2 Environmental precautions



GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

ENVIRONMENTAL PRECAUTIONS

Stop gas leak if possible without any risk.

6.3 Methods and material for containment and cleaning up

METHODS AND MATERIAL

Ventilate thoroughly.

6.4 Reference to other sections

7 Handling and Storage

7.1 Precautions for safe handling

PRECAUTION FOR SAFE HANDLING

The equipment must be earthed. NOT TRANSLATEDNOT TRANSLATED

7.2 Conditions for safe storage, including any incompatibilities

CONDITION FOR SAFE STORAGE, INCLUDING ANY UNCOMPATIBILITIES

Keep away from sources of ignition. Read and follow manufacturer 's recommendations! Store isolated from oxidizing materials. Keep container tightly closed. Use only in well-ventilated areas. Store at temperatures below 50 °C.

7.3 Specific end uses

8 Exposure controls / Personal protection

8.1 Control parameters

8.2 Exposure controls

APPROPRIATE ENGINEERING CONTROLS

Use only in well-ventilated areas. When using do not smoke.

EYE PROTECTION

Use approved safety goggles or face shield.

SKIN PROTECTION

Wear protective clothing.

HAND PROTECTION

Wear suitable gloves.

9 Physical and chemical Properties

9.1 Information on basic physical and chemical properties

PHYSICAL STATE Gas.

COLOUR Colourless.

ODOUR Garlic.

WATER SOLUBILITY mg/l



GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

| Parameter | Value/unit | Method/reference | Observation |
|---|--------------|------------------|-------------|
| pH consentrate | No data | | |
| pH in solution | No data | | |
| Melting point | 84 - 88,8 °C | | |
| Freezing point | No data | | |
| Initial boiling point and boiling range | No data | | |
| Flash point | No data | | |
| Evaporation rate | No data | | |
| Flammability (solid, gas) | No data | | |
| Flammability limits | No data | | |
| Explotion limits | No data | | |
| Vapour pressure | 44 mbar | 20°C | |
| Vapour density | No data | | |
| Relative density | 0,9 | I mättad luft | |
| Partition coefficient | No data | | |
| Auto-ignition temprature | 325 °C | | |
| Decomposition temprature | No data | | |
| Viscosity | No data | | |

9.2 Other safety information

| Parameter | Value/unit | Method/reference | Observation |
|---------------------|--------------------|------------------|-------------|
| Molecular weight | 26 g/mol | | |
| Kritisk temperatur | 35°C | | |
| Brännbarhetsgränser | 2,4-83 vol% i luft | | |

| | Note no. | comments |
|--|----------|----------|
|--|----------|----------|

10 Stability and Reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

POSSIBILITY OF HAZARDOUS REACTIONS

Forms explosive mixtures with air. Reacts strongly with oxidizers.

10.4 Conditions to avoid

CONDITIONS TO AVOID

NOT TRANSLATEDNOT TRANSLATED

10.5 Incompatible materials

10.6 Hazardous decomposition products:

11 Toxicological information

11.1 Toxicological effects

12 Ecological information

12.1 Toxicity

12.2 Persistence and degradability



GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

13 Disposal considerations

13.1 Waste treatment methods

GENERAL REGULATIONS

NOT TRANSLATEDForms explosive mixtures with air. Prevent liquid from running into watercourses, drains, cellars and work pits. Contact supplier for disposal information.

14 Transport information

Classified as Dangerous Goods: Yes

| Land transport (ADR/RID) | | | | |
|--------------------------|------|---------------|--|--|
| 14.1 UN-No. | 1001 | 14.4 Packing | | |
| | | group | | |
| 14.2 Proper | | 14.5 | | |
| Shipping | | Environmental | | |
| Name | | hazards | | |
| 14.3 | 2.1 | | | |
| Class(es) | | | | |
| Hazard | | | | |
| label(s) | | | | |
| Hazard ID: | | Tunnel | | |
| | | restriction | | |
| | | code | | |

| Inland water ways transport (ADN) | | | | |
|--|------|-----------------------|--|--|
| 14.1 UN-No. | 1001 | 14.4 Packing group | | |
| 14.2 Proper | | 14.5 | | |
| Shipping | | Environmental | | |
| Name | | hazards | | |
| 14.3 Class(es) | 2.1 | | | |
| Enviromentally hazardous in tank-vessels | | | | |

| Sea transport | (IMDG) | |
|---------------|--------|-----------------------|
| 14.1 UN-No. | 1001 | 14.4 Packing group |
| 14.2 Proper | | 14.5 |
| Shipping | | Environmental |
| Name | | hazards |
| 14.3 | 2.1 | |
| Class(es) | | |
| Sub Risk: | | |
| IMDG Code | | |
| segregation | | |
| group | | |
| Marine | No | |
| pollutant | | |
| EMS: | | |



GASBEHÅLLARE ACETYLEN 21150107

Last changed: 31/05/2012 Internal No: 21150107

Air transport (ICAO-TI / IATA-DGR)

14.1 UN-No. 1001 14.4 Packing

group 14.5

14.2 Proper Shipping Environmental

Name hazards

14.3 2.1

Class(es) Hazard label(s)

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical Safety Assessment

16 Other information

LIST OF RELEVANT R-PHRASES

R12 Extremely flammable.

R5 Heating may cause an explosion.

R6 Explosive with or without contact with air.

LIST OF RELEVANT H-STATEMENTS

H220 Extremely flammable gas. H240 Heating may cause an explosion.

EUH006 Explosive with or without contact with air.