

Material Safety Data Sheet

1 Chemical Product and Company Identification

SHANGHAI WANHONG POWER AND ENERGY CO.,LTD.

Building 4, No.1288 Yecheng Road, Jiading District, Shanghai.

Tel:+862133517961 Fax:+862133517598

2. Composition/ Information on Ingredients

The products referenced herein are exempt articles and are not subject to OSHA's Hazard Communication Standard requirements.

This information sheet is provided as a service to our customers.

Chemical/Size	SC1500 battery
Weight	≤45g
Mercury	< 1ppm
Cadmium	< 5ppm
Lead	< 10ppm
Nickel hydroxide	22.11%
hydrogen storage alloy	28.38%
nickel	3.38%
Steel	30.82%
Plastic	3.20%
Potassium hydroxide	3.47%
Water	8.11%
other	0.53%
	100%

The components in this section may only represent a hazard, if the batteries are damaged.

Dangerous components: none

3. Hazards Identification:

Warning: When recharge batteries or discard in the fire or use used battery with new one, or connected improperly may cause battery vent, leak or explode.

Damaged batteries may cause skin and eye burn, may cause respiratory tract irritation.

4. First-aid Measure

General speaking it is not expected to result in situation that requires first-aid measure, except the damaged batteries may cause they release the contents.

Inhalation: If vapours or fumes from vented or leaked batteries are irritation, move to fresh air and get medical attention.

Eyes: Check for and remove any contact lens, flush eyes with plenty of water, holding eyelids open, for at least 20 minutes, get medical help.

Skin: Immediately move the metal fragments and chemical components flush skin with plenty of water at least 15 minutes, get medical, if necessary,

Ingestion: Get immediately medical attention, do not induce vomiting or give a liquid to unconscious person.

5. Fire Fighting Measure:

Extinguishing media: Use appropriate agent for adjacent fire.

Flash point: Not available

Auto-ignition temperature: Not available

Flammable limits: Not available

Products of combustion: Zinc oxide, manganese oxide.

6. Accidental Release Measure:

Not available

7. Handling and Storage:

Precaution: Handling and transfer the products with care, make sure the packing always in good condition.

Damaged packing may cause batteries contact together, in this case batteries may short circuit or improperly connected, it cause batteries venting, leaking or exploding.

Storage: Store in a dry, cool and well-ventilated area.

8. Exposure control / Personal protection

Exposure control: If necessary, set local exhaust ventilation.

Personal protection: Gloves, safety glass, dust respirator.

9. Physical and Chemical Properties

Physical State and Appearance: Solid

Melting Point : Not applicable

Vapour pressure: Not available.

PH (1% soln/water): Not available.

Solubility: Insoluble.

Volatility: Not available.

Specific gravity: (water=1) SC1500 battery X=2.47

Odour: Odourless.

Taste: Not available.

10. Stability and Reactivity

Stability: The products are stable

Instability temperature: Not available.

Incompatibility: Reactive with acids and alkalis.

Corrosivity: None.

Hazardous Polymerization: Will not occur.

11. Toxicological information

Note: Since the materials in this battery are sealed in the can, the potential for exposure to the components of the battery is negligible, when the battery is used as directed. However technical or electrical abuse of the battery may result in the release of battery contents.

Toxicity to Animals: Not applicable

Chronic Effects on Human: Not applicable.

12. Ecological information

This product has not been tested for environmental effects.

13. Disposal consideration

Waste disposal: Consult your local or regional authorities, disposal maybe subject to national, state, or local laws.

14. Transport information

Shanghai Wanhong Power and Energy Co.,Ltd

The goods is not subject to IMO IMDG CODE and not dangerous cargo, subject transport by sea. The goods are packaged to the packaging requirements of ordinary goods.

15. Regulatory information

IARC: International Agency for Research Cancer.

NPT: US National Toxicology Program.

NIOSH: National Institute of Occupational Safety and Health

ACGIH, documentation on TLVS and BELS 1992-1993

ACGIH, threshold limit values, current listing

16. Other information

Warning wordings: "Keep out reach of children"

"Do not recharge or discard in fire or use used battery with new one, make sure polarity"
