

Skruvnycklar

Välj rätt nyckelvidd



Skrudar ISO (= standard)

Metrisk (SS-ISO 272)				Unified (SS-ISO 272)				Tråskruv (SS 2020) (DIN 571)	
	M 6 S sexkant- skruv	M 6 SF sexkantskruv med fläns	SB Stålbyggn.- skruv		U 6 S sexkant- skruv	SB Stålbyggn.- skruv		T 6 S sexkant tråskruv (s.k.Fransk)	
Gänga	N	N	N	Gänga UNC- UNF	N	N	Gänga	N	
M 1,6	3,2								
M 1,8	3,2								
M 2	4								
M 2,2	4								
M 2,5	5								
M 3	5,5	5 7							
M 3,5	6 (5,5)								
M 4	7								
M 4,5	7	7 9,5							
M 5	8	7 8 11							
M 6	10	8 10 10 13,8		1/4	7/16 11,11		M 6	10	
M 7	11								
M 8	13	10 12 17,7		5/16	1/2 12,7		M 8	13	
M 10	16 (17)	13 14 21,6		3/8	9/16 14,29		M 10	16 (17)	
M 12	18 (19)	15 26,6	18 (19)	1/2	3/4 19,05	3/4 19,05	M 12	18 (19)	
M 14	21 (22)	18 19 30							
M 16	24	21	24	5/8	15/16 23,81	15/16 23,81	M 16	24	
M 18	27								
M 20	30	27	30	3/4	1 1/8 28,58	1 1/8 28,58	M 20	30	
M 22	34 (32)		34 (32)	7/8	1 5/16 33,34	1 5/16 33,34			
M 24	36		36	1	1 1/2 38,1	1 1/2 38,1			
M 27	41								
M 30	46			1 1/4	1 7/8 47,63				
M 33	50								
M 36	55			1 1/2	2 1/4 57,15				
M 39	60								
M 42	65								
M 45	70								
M 48	75			1 3/4	2 5/8 66,68				
M 52	80			2	3 76,2				
M 56	85								
M 60	90								
M 64	95								
M 68	100								
M 72	105								
M 76	110								
M 80	115								
M 85	120								
M 90	130								
M 95	135								
M 100	145								
M 105	150								
M 110	155								
M 115	165								
M 120	170								
M 125	180								
				Uppgifter inom parentes avser äldre standard (1985). Skruvar med flera måttuppgifter för nyckelvidd = avviker mellan olika fabrikat.					